



# TECHNICAL

GRZEGORZ TĘGOS

## Technika Napędu i Transmisji Mocy

[www.technical.pl](http://www.technical.pl)

e-mail: [biuro@technical.pl](mailto:biuro@technical.pl)

tel. +48 63 27 25 487; +48 63 26 16 257

## Taper Lock - Taper Busch

otwory: metryczne i calowe





## SER-SIT® conical bushing: slip torques and allowable axial load

The slip torques have been calculated considering the nominal tightening torque for the screws (Ms), a friction coefficient value  $\eta = 0,14$  and in case of assembly without keyway.

Taper Bushing SER-SIT®	Bore diameter d [mm]	Slip torque [Nm]	Allowable axial load [N]
1008	12	29	3990
	19	51	4940
	24	66	5490
1108	12	28	-
	19	49	4630
	24	64	5220
	28	79	5720
1210 + 1215	16	82	8840
	19	105	9800
	24	142	10900
	32	210	12300
1610 + 1615	19	98	-
	24	135	9570
	38	240	11900
	42	265	12700
2012	24	165	11500
	38	310	14400
	42	340	15700
	48	400	-
	50	420	16700
2517	24	220	-
	38	380	17000
	42	430	18500
	48	510	-
	55	600	21000
	60	670	22300
3020 + 3030	38	520	23900
	48	730	26100
	55	890	29900
	60	970	31500
	75	1300	34500
3535	42	1000	41000
	60	1580	49800
	75	2150	54800
	90	2600	59000
4040	48	1700	-
	60	2300	70200
	75	3150	77200
	100	4400	89400
4545	55	2500	79600
	75	3900	93000
	100	5500	107700
	110	6300	-
5050	75	3950	91800
	100	5650	106600
	125	7370	119500